



Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 10/14/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Azo Grout 675

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Water stop

1.3. Supplier

Azon USA Inc.
2204 Ravine Rd
Kalamazoo, Michigan 49004
USA
T 269-385-5942

1.4. Emergency telephone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)
CCN 2189

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (inhalation:dust,mist) Category 4	Harmful if inhaled
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Respiratory sensitization, Category 1	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, Category 1	May cause an allergic skin reaction
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
Harmful if inhaled
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	<p>May cause respiratory irritation Suspected of causing cancer May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation)</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors, gas. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, face protection, protective clothing, protective gloves. [In case of inadequate ventilation] wear respiratory protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p>
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available.

2.4. Unknown acute toxicity (GHS US)

No additional information available.

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Dimethyl Glutarate	CAS-No.: 1119-40-0	14 – 22	Eye Irrit. 2A, H319
4,4'-Methylenediphenyl diisocyanate	CAS-No.: 101-68-8	1 – 5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Dimethyl Adipate	CAS-No.: 627-93-0	1.5 – 7.5	Eye Irrit. 2, H319
Dimethyl Succinate	CAS-No.: 106-65-0	1.5 – 7.5	Eye Irrit. 2, H319

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Diphenylmethane Diisocyanate, isomers and homologues	CAS-No.: 9016-87-9	1 – 5	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Toluene-diisocyanate (mixed isomers)	CAS-No.: 26471-62-5	0.5 – 2	Acute Tox. 2 (Inhalation), H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 Aquatic Chronic 3, H412
4-Isocyanatosulphonyltoluene	CAS-No.: 4083-64-1	> 0.6	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 Aquatic Chronic 3, H412
2,4'-Diphenylmethane Diisocyanate (MDI)	CAS-No.: 5873-54-1	0.1 – 1	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: First aider: Pay attention to self-protection. Never give anything by mouth to an unconscious person. Give artificial respiration if necessary. Induce artificial respiration with mask fitted with one-way valve or other suitable device but not mouth-to-mouth. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim is unconscious : Lay in a stable manner on victim's side. Induce artificial respiration with mask fitted with one-way valve or other suitable device; not mouth-to-mouth. Call a physician immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. If the person is fully conscious, make him/her drink water (8 ounces / 240mL). Never give an unconscious person anything to drink. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use. Ingestion may cause nausea and vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical, CO ₂ , dry sand, or alcohol-resistant foam. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers from fire area if it can be done without personal risk. Use water spray or fog for cooling exposed containers. Use extinguishing media appropriate for surrounding fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all personal contact including breathing in the mist, spray, vapors, gas. Do not take actions involving personal risks. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, remove ignition sources, ventilate area. Avoid contact with skin and eyes. Avoid breathing mist, spray, vapors, gas. Prevent other non-emergency personnel from entering the danger area.

6.1.2. For emergency responders

Protective equipment	: Wear the recommended personal protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. Ventilate spillage area. Stop leak if safe to do so. Remove all sources of ignition.

6.2. Environmental precautions

Do not let the product reach soil, drains, sewers, or surface and ground water.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Small spills: Contain with non-combustible inert absorbent. In case of large spillages: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Absorb spilled material with sand or earth.
- Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing mist, spray, vapors, gas. Avoid contact with skin, eyes and clothing. Take precautionary measures against static discharge.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a cool, dry and well-ventilated area away from incompatible substances. Store locked up. Store tightly closed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
- Incompatible products : Oxidizing agents.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Azo Grout 675

No additional information available.

4,4'-Methylenediphenyl diisocyanate (101-68-8)

USA - ACGIH - Occupational Exposure Limits

Local name	Methylene bisphenyl isocyanate (MDI)
ACGIH OEL TWA	0.005 ppm
Remark (ACGIH)	TLV® Basis: Resp sens
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Methylene bisphenyl isocyanate (MDI)
OSHA PEL C	0.2 mg/m ³

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4,4'-Methylenediphenyl diisocyanate (101-68-8)

	0.02 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Toluene-diisocyanate (mixed isomers) (26471-62-5)

No additional information available.

4-Isocyanatosulphonyltoluene (4083-64-1)

No additional information available.

2,4'-Diphenylmethane Diisocyanate (MDI) (5873-54-1)

No additional information available.

Dimethyl Glutarate (1119-40-0)

No additional information available.

Dimethyl Adipate (627-93-0)

No additional information available.

Dimethyl Succinate (106-65-0)

No additional information available.

Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)

No additional information available.

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use general ventilation, local exhaust ventilation, or process enclosure to keep the airborne concentrations below the permissible exposure limits.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment. Wear recommended personal protective equipment.

Materials for protective clothing:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment.

Hand protection:

Wear protective gloves. Wear suitable gloves resistant to chemical penetration. Discard contaminated gloves and wash contaminated clothing before reuse

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Long sleeved protective clothing. Body protection should be chosen depending on activity and possible exposure

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Clear liquid.
Color	: Amber Light brown
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93.3 °C / 200 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.09 – 1.12
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 725 – 1025 cP (25 °C/ 77 °F)
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

Azo Grout 675

ATE US (dust, mist)	1.566 mg/l/4h
---------------------	---------------

4,4'-Methylenediphenyl diisocyanate

LD50 oral rat	9200 mg/kg body weight
---------------	------------------------

Toluene-diisocyanate (mixed isomers)

LD50 dermal rabbit	> 9400 mg/kg body weight
--------------------	--------------------------

4-Isocyanatosulphonyltoluene

LD50 oral rat	2330 mg/kg body weight
---------------	------------------------

LD50 dermal rat	> 2000 mg/kg body weight
-----------------	--------------------------

Dimethyl Glutarate

LD50 oral rat	8900 mg/kg body weight
---------------	------------------------

LD50 dermal rat	> 2000 mg/kg body weight
-----------------	--------------------------

LC50 Inhalation - Rat	Based on a related compound: not expected to be an inhalation hazard
-----------------------	--

Dimethyl Adipate

LD50 oral	8500 mg/kg body weight (mouse)
-----------	--------------------------------

LD50 dermal rat	> 2000 mg/kg body weight
-----------------	--------------------------

LD50 dermal rabbit	> 5000 mg/kg body weight
--------------------	--------------------------

LC50 Inhalation - Rat	Based on a related compound: not expected to be an inhalation hazard
-----------------------	--

Dimethyl Succinate

LD50 oral rat	> 5000 mg/kg
---------------	--------------

LD50 dermal rat	> 2000 mg/kg body weight
-----------------	--------------------------

LD50 dermal rabbit	> 5000 mg/kg
--------------------	--------------

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diphenylmethane Diisocyanate, isomers and homologues	
LD50 oral rat	49 g/kg
LD50 dermal rabbit	> 9400 mg/kg body weight
LC50 Inhalation - Rat	490 mg/m ³
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Dimethyl Adipate	
Serious eye damage/irritation, rabbit	Moderately irritating
Diphenylmethane Diisocyanate, isomers and homologues	
Serious eye damage/irritation, rabbit	Mildly irritating
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
4,4'-Methylenediphenyl diisocyanate	
IARC group	3 - Not classifiable
Toluene-diisocyanate (mixed isomers)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
Diphenylmethane Diisocyanate, isomers and homologues	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
4,4'-Methylenediphenyl diisocyanate	
STOT-single exposure	May cause respiratory irritation.
Toluene-diisocyanate (mixed isomers)	
STOT-single exposure	May cause respiratory irritation.
4-Isocyanatosulphonyltoluene	
STOT-single exposure	May cause respiratory irritation.
2,4'-Diphenylmethane Diisocyanate (MDI)	
STOT-single exposure	May cause respiratory irritation.
Diphenylmethane Diisocyanate, isomers and homologues	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).
4,4'-Methylenediphenyl diisocyanate	
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (Inhalation).

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,4'-Diphenylmethane Diisocyanate (MDI)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Diphenylmethane Diisocyanate, isomers and homologues	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Toluene-diisocyanate (mixed isomers)	
Viscosity, kinematic	2.221 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
2,4'-Diphenylmethane Diisocyanate (MDI)	
Viscosity, kinematic	4.002 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: Stinging, redness, itching, tears, blurred vision, swelling.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use. Ingestion may cause nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

4,4'-Methylenediphenyl diisocyanate	
NOEC (chronic)	≥ 10 mg/l
Toluene-diisocyanate (mixed isomers)	
LC50 - Fish [1]	133 mg/l
EC50 - Crustacea [1]	12.5 mg/l
EC50 - Other aquatic organisms [1]	18.3 mg/l
EC50 96h - Algae [1]	3230 mg/l
EC50 96h - Algae [2]	4300 mg/l
LOEC (chronic)	2.2 mg/l
NOEC (chronic)	1.1 mg/l
4-Isocyanatosulphonyltoluene	
LC50 - Fish [1]	> 45 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	30 mg/l
EC50 72h - Algae [2]	25 mg/l
2,4'-Diphenylmethane Diisocyanate (MDI)	
NOEC (chronic)	≥ 10 mg/l

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dimethyl Glutarate	
LC50 - Fish [1]	13400 mg/l
EC50 - Crustacea [1]	3940 – 4670 mg/l
Dimethyl Adipate	
LC50 - Fish [1]	87.095 mg/l
EC50 - Crustacea [1]	72 mg/l
EC50 72h - Algae [1]	> 100 mg/l
EC50 96h - Algae [1]	6.691 mg/l
Dimethyl Succinate	
LC50 - Fish [1]	50 mg/l
EC50 - Crustacea [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
EC50 96h - Algae [1]	11.917 mg/l
NOEC (chronic)	358.6 mg/l

12.2. Persistence and degradability

Azo Grout 675	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Azo Grout 675	
Bioaccumulative potential	Not established.

Dimethyl Glutarate	
Partition coefficient n-octanol/water (Log Pow)	0.62

Dimethyl Adipate	
Partition coefficient n-octanol/water (Log Pow)	1.03

Dimethyl Succinate	
Partition coefficient n-octanol/water (Log Pow)	0.35

12.4. Mobility in soil

Dimethyl Adipate	
Mobility in soil	10.9

12.5. Other adverse effects

No additional information available.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations. Refer to all applicable national, international and local regulations or provisions.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Azo Grout 675

SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
-------------------------------------	--

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Toluene-diisocyanate (mixed isomers)	CAS-No. 26471-62-5	0.5 – 2%
--------------------------------------	--------------------	----------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

4,4'-Methylenediphenyl diisocyanate	CAS-No. 101-68-8	1 – 5%
Toluene-diisocyanate (mixed isomers)	CAS-No. 26471-62-5	0.5 – 2%
Diphenylmethane Diisocyanate, isomers and homologues	CAS-No. 9016-87-9	1 – 5%

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

Toluene-diisocyanate (mixed isomers) (26471-62-5)

CERCLA RQ	100 lb
-----------	--------

15.2. International regulations

CANADA

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Listed on the Canadian DSL (Domestic Substances List)

Toluene-diisocyanate (mixed isomers) (26471-62-5)

Listed on the Canadian DSL (Domestic Substances List)

4-Isocyanatosulphonyltoluene (4083-64-1)

Listed on the Canadian DSL (Domestic Substances List)

2,4'-Diphenylmethane Diisocyanate (MDI) (5873-54-1)

Listed on the Canadian DSL (Domestic Substances List)

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dimethyl Glutarate (1119-40-0)

Listed on the Canadian DSL (Domestic Substances List)

Dimethyl Adipate (627-93-0)

Listed on the Canadian DSL (Domestic Substances List)

Dimethyl Succinate (106-65-0)

Listed on the Canadian DSL (Domestic Substances List)

Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available.

National regulations

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Toluene-diisocyanate (mixed isomers) (26471-62-5)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Dimethyl Glutarate (1119-40-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Dimethyl Succinate (106-65-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



WARNING:

This product can expose you to Toluene-diisocyanate (mixed isomers), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Issue date: 10/14/2024

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources

: SDS prepared by CHEMTREC.

Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit


Azo Grout 675

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.